

cobas® p 512 pre-analytical system

Technical specifications



System description

Basic System

cobas® p 512 pre-analytical system

08479763001

Basic Specifications

- Continuous loading of tubes
- Simultaneous loading of different tube types
- Prioritization of urgent samples
- Registration of samples
- Comprehensive inspection of sample quality
 - Tube type identification via tube dimensions & cap color
(used to cross-check the tube type with the test request and/or specimen)
 - Liquid level check and sample volume calculation through 3 barcode label
 - Spin status detection
- Decapping of tubes
- Simultaneous decapping of hemogard, screw and rubber stopper caps
- Removal of caps with a twist and pull motion to prevent build-up of aerosols
- Sorting according configurable sorting criteria, including utilizing sample quality check information for error handling
- Flexible and freely definable input and output areas:
 - Into and out of racks
 - Out of centrifuge buckets
- Definable output areas for tubes with specific errors
(e.g. barcode not readable, no test requests)
- First pass and recursive workflow
- Automatic barcode alignment of tubes for reading and sorting
- Archiving of samples

Options	Possibility to connect to CCM with different rack configurations.	Multiple material numbers
	Bulk Loader Input Module for cobas p 512 and cobas ® p 612	09469761001
	Bulk Loader Input Module for cobas ® p 471 and cobas ® p 671	09469460001
	cobas p 471 centrifuge unit	07563787001
	cobas p 671 centrifuge unit	07563795001
Optional Specifications	<ul style="list-style-type: none"> • Bulk loading of samples • Centrifugation of samples (connection to single or double centrifuge) • Recognition of sample quality into 5 different user-defined categories (serum ok, light hemolytic, hemolytic, lipemic, icteric) • Capture of sample image 	
Specifications		
Throughput	Up to 1400 tubes per hour (basic system)	
Sample identification	<ul style="list-style-type: none"> • Positive sample identification via barcode • Barcode types supported: Codabar, 2 of 5 interleaved (ITF), Code 39, Code 128 (incl. ISBT 128), others* 	
Input / Output Capacity	<ul style="list-style-type: none"> • Input: 600 samples, 4 drawers, up to 30 targets • Output: 1200 samples; 8 drawers, up to 41 targets 	
Tube types	<p>Supports established tubes for hematology, coagulation, serum, plasma and urine manufactured by BD, Sarstedt, Kabe, Greiner, Terumo and others tube vendors</p> <ul style="list-style-type: none"> • Accepts most 3, 5, 7 and 10 mL plastic tubes • Uses qualified tubes (list with qualified tubes is available from your distributor) • Tubes can be qualified on request 	
Sample carriers	Supports racks supplied from Roche and other vendors	<ul style="list-style-type: none"> • Analyzer racks • Archive racks • Centrifuge buckets
Dimensions	<ul style="list-style-type: none"> • Width: approx. 2.39 m (94.1") • Depth: approx. 1.41 m (55.5") • Height: approx. 1.84 m (72.4") 	<ul style="list-style-type: none"> • Weight: approx. 744 kg (1640 lbs) <p>Control unit is incorporated on the system</p>
Operating conditions	<ul style="list-style-type: none"> • Designed for indoor operation up to 2000 meters above sea level • Ambient temperature +15 °C to +30 °C (+59 °F to +86 °F) 	<ul style="list-style-type: none"> • Relative humidity 20 % to 80 % • Power consumption: approx. 800 W • Voltage: 230 V, 50/60 Hz (fuse 6.3 AH) and 115 V, 50/60 Hz (fuse 10 AH)
Compressed air	<ul style="list-style-type: none"> • Dry and oil free • Air pressure: min. 6.5 bar (94 psi) to max. 8.0 bar (116 psi) • Air consumption: approx. 94 l/min (24.8 gals/min), with recapper 	
Interface	<ul style="list-style-type: none"> • ASTM protocol • Network connection via RS 232 and Ethernet • Remote access for diagnosis and service 	
Safety marks	CE, ETL	

* Other barcode types can be checked on request

COBAS is a trademark of Roche.

© 2024 Roche

Published by:

Roche Diagnostics International Ltd

CH-6343 Rotkreuz

Switzerland

[More info on diagnostics.roche.com](https://www.roche.com/diagnostics)